



Food thermometer CATERTEMP

Thermometer designed especially for professional chefs looking for a simple tool that allows them to meet the standards for food handling, it also has the "Hold" function that keeps any reading on-screen. It includes a stainless steel probe with a 1m polyurethane wire.

STANDARD PARAMETERS

Sensor element: K type thermocouple
Measuring range: -49.9 to 299.9°C
Scale: Celsius (°C)
Resolution: 0.1°C
Accuracy: $\pm 0.4^{\circ}\text{C}$ (-50 y 199°C) other $\pm 1^{\circ}$
Battery: 3x 1.5 volts AAA
Battery life: 10.000 hours
Dimensions: 25x56x128mm
Probe dimension: $\varnothing 3.3 \times 130\text{mm}$
Wire: 1m coiled
Weight: 130g

MATERIALS

Housing: ABS plastic with Biomaster	Wire: Polyurethane
Display: LCD 12mm	

Reference: 221-046

Application:

•Catering



Food thermometer THERMAMITE

Thermometer designed especially for professional chefs looking for a simple, accurate and inexpensive tool that allows them to meet the standard for food handling. It includes a stainless steel probe with a 500mm PVC wire.

STANDARD PARAMETERS

Sensor element: K type thermocouple
Measuring range: -50 to 300°C
Scale: Celsius (°C)
Resolution: 1°C
Accuracy: $\pm 1^{\circ}\text{C} \pm 1\%$
Battery: 3x 1.5 volts AAA
Battery life: 10.000 hours
Dimensions: 25x56x128mm
Probe dimension: $\varnothing 3.3 \times 100\text{mm}$
Wire: 0.5m
Weight: 130g


MATERIALS

Housing: ABS plastic with Biomaster	Wire: PVC
Display: LCD 12mm	

Reference: ☐ 261-010
☒ 261-020
☐ 261-030
☐ 261-040
☐ 261-050

Application:

•Catering



Catering thermometer FOODCHECK

Thermometer designed especially for professional chefs looking for a simple, accurate and inexpensive tool that allows them to meet the standard for food handling. It includes a stainless steel probe with a 500mm PVC wire.

STANDARD PARAMETERS

Sensor element: K type thermocouple
Measuring range: -49.9 to 299.9°C
Scale: Celsius (°C)
Resolution: 0.1°C
Accuracy: $\pm 0.4^{\circ}\text{C}$ (-50 to 199°C) other $\pm 1^{\circ}$
Battery: 3x 1.5 volts AAA
Battery life: 10.000 hours
Dimensions: 25x56x128mm
Probe dimension: $\varnothing 3.3 \times 130\text{mm}$
Wire: 0.5m
Weight: 130g

MATERIALS

Housing: ABS plastic with Biomaster	Wire: PVC
Display: LCD 12mm	

Reference: ☐ 221-018
☒ 221-028
☐ 221-038
☐ 221-048
☐ 221-058

Application:

•Catering

