

## Portable thermometers with penetration probe

## Digital

**Application:** 

· General



#### ispidy. Eden dine includes d

Portable thermometer with penetration stainless steel probe with dimensions  $\emptyset 3.5x120$ mm. The instrument has a "Hold" button to keep a fixed temperature in display. Each unit includes a protective sheath with a pocket clip.

#### STANDARD PARAMETERS

Sensor element: Thermistor Measuring range: -49.9 to 299.9°C

Scale: Celsius (°C)
Resolution: 0.1°C

Accuracy: ±1°C (-19.9 y 119.9 ) other ±2°C

Pocket thermometer with Hold function

Battery: 1x button cell 1.5 volts LR44
Battery life: 6.000 hours
Dimensions: 17x20x190mm

Weight: 28g

### Reference: Digital 9.3

#### **MATERIALS**

Housing: ABS plastic
Display: LCD 6mm

# Hold



**Application:** 

· Catering



#### Waterproof pocket thermometer

This thermometer is a handy pocket-sized thermometer. Include a reduced tip stainless steel probe that enables a quick reading of the temperature. It registers maximum and minimum temperatures. Each unit includes a protective sheath with a pocket clip.

#### STANDARD PARAMETERS

Sensor element: Thermistor

Measuring range: -49.9 to 199.9°C

Scale: Celsius-Fahrenheit (°C/F)

Resolution: 0.1°C/F

Accuracy: ±0.5°C (-9.9 y 99.9°C ) other ±1° Battery: 1x 3 volts CR2032 lithium coin cell

Battery life: 5.000 hours

Dimensions: Ø41x17x175mm Probe dimension: Ø2.5x125mm

Weight: 22g

### MATERIALS

Housing: ABS plastic
Display: LCD 8.5mm

IP65



Application:

DishwasherCatering



#### Dishwasher thermometer

It can be placed inside a dishwasher to ensure that maximum cycle temperature is correct. It can be used as a conventional food thermometer. The portable compact thermometer features a pointed stainless steel probe. Each unit includes a protective silicone boot and sheath with a pocket clip and a wall-mounting keyhole slot.

#### STANDARD PARAMETERS

Sensor element: Thermistor

Measuring range: -49.9 to 199.9°C

Scale: Celsius-Fahrenheit (°C/F)

Resolution: 0.1°C/F

Accuracy: ±0.5°C (-9.9 y 99.9°C) other ±1.5° Battery: 1x 3 volts CR2032 lithium coin cell

Battery life: 5.000 hours

Dimensions: 20x26x200mm Probe dimension: Ø2.5x122mm

Weight: 25g

#### MATERIALS

Housing: ABS plastic
Display: LCD 8mm









Reference: 810-275





